

## V-Belt Spray

### Description

Special combination of active ingredients formulated for maintaining and increasing the efficiency and performance of V-belt drives on vehicle engines, compressors, pumps and all other drives with V-belts.

### Properties

- high efficiency
- multifunctional uses
- prevents aging
- care and protection
- protects belts and pulleys from wear
- prevents belt slip
- eliminates squeaks
- not suitable for flat belts

### Technical data

|                             |  |
|-----------------------------|--|
| Color / appearance          | orange                                 |
| Base                        | adhesive dissolved in petroleum spirit |
| Operating temperature range | -20 bis ca. 70 °C                      |
| Odor                        | characteristic                         |
| Form                        | aerosol, liquid                        |
| Flash point                 | -60 °C                                 |

### Areas of application

For V-belts made of leather, rubber, balata, hair, etc.  
Not suitable for flat belts.

### Application

Spray the lateral bonding surfaces of the V-belt from a distance of approx. 20 cm and allow to react for approx. 10 min. before recommissioning. If a thicker layer is desired, repeat the process.

### Available pack sizes

|                    |                        |
|--------------------|------------------------|
| 400 ml Can aerosol | 1841<br>D-NL-F-GR-ARAB |
| 400 ml Can aerosol | 2834<br>GB-DK-FIN-N-S  |
| 400 ml Can aerosol | 4085<br>D-GB-I-E       |

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

