

PTFE OIL SPRAY

HIGH-PERFORMANCE LUBRICANT

Description

The fully synthetic PTFE OIL SPRAY combines the characteristics of an oily lubricant with those of a dry PTFE-based lubricant. The micronised PTFE particles offer outstanding emergency running properties. Low coefficient of friction, undermines and repels water.

Field of application

MOTOREX PTFE OIL SPRAY can be used universally. It is particularly recommended where a long-lasting lubricating effect is required. It is also very good for long-term use where plastics are paired with metals.

Application

Shake the can well before use until the mixing ball is moving freely. Briefly spray the area in question from a distance of 10–20 cm and leave to dry.

Advantages

- · long-term effect
- outstanding emergency running properties
- Dielectric
- Fully synthetic base oil
- · Contains PTFE particles
- · Highly resistant to chemicals
- · Friction-reducing additives

Sizes

500ml

MOTORES MOTORES

mofakult ch

modela ilt ob

mofakult.ch

ofakult.ch 💭

	SAP-Nr.	Product name	packaging unit
ŀ	305330	PTFE OIL SPRAY 500ML D00	1 x 500ml
	305331	PTFE OIL SPRAY 500ML K12	12 x 500ml

lasticals and a second state of the state of

mofakult.ch



erstellt am: 08.02.21